



LENGTH

Up to 30 ft

LEVEL CAPACITY

Up to 780 ft³

HEAPED CAPACITY

Up to 975 ft³

CARRYING CAPACITY

Up to 72,000 lbs

EMPTY WEIGHT

Up to 25,000 lbs

SUSPENSION

Spring

NARROW BODY SPREADER

ENGINEERED TO HANDLE EVEN THE SMALLEST SPACES.

Don't compromise on field compaction or capacity.

The Narrow Body Manure Spreader gets the toughest jobs done faster and easier with our spreader designed to operate in more confined spaces like feedlots.

Featuring the same innovative technology and durable fully-welded components as our Wide Body machines, it's guaranteed to function at the highest standard.

NARROW BODY SPECIFICATIONS

	VM2248-23	VM2448-23	VM2648-23	VM3048-36
DIMENSIONS				
Overall Length	9.68 m 381 in	10.29 m 405 in	10.9 m 429 in	12.1 m 477 in
Overall Height	3.56 m 140 in			
Overall Width	2.72 m 107 in			
Inside Box Width	1.98 m 78 in			
Inside Box Length	6.1 m 240 in	6.71 m 264 in	7.32 m 288 in	8.52 m 338 in
Load Height	2.82 m 111 in			2.84 m 112 in
Level Capacity	16.2 m ³ 572 ft ³	17.7 m ³ 624 ft ³	19.1 m ³ 676 ft ³	22.1 m ³ 780 ft ³
Heaped Capacity	20.2 m ³ 715 ft ³	22.1 m ³ 780 ft ³	23.9 m ³ 845 ft ³	27.6 m ³ 975 ft ³
Carrying Capacity	46,000 lbs 20,865 kg	46,000 lbs 20,865 kg	46,000 lbs 20,865 kg	72,000 lbs 32,659 kg
Empty Weight	16,500 lbs 7,484 kg	17,500 lbs 7,938 kg	18,500 lbs 8,391 kg	25,000 lbs 11,340 kg
STANDARD FEATURES				
Box Construction	10 Gauge			
Suspension	Spring			
Axle	Tandem			Tridem
Tire Size	700/40-22.5			
Tire Options	Yes		No	
End Gate	Guillotine			
Bulkhead	Standard			
Hitch Type	Standard or Equal Angle			
Decal Package	Premium			
APRON/FLOOR				
Long-Link 5/8" Grade 100 Floor Chain	Yes			
Galvanized & Removable Cross Slats	Yes			
Floor Drive	Single	Dual		
UHMW Plastic Floor	Yes			
Steel Idler Sprocket with Bronze Brushings	Yes			
BEATERS				
Vertimax Vertical Beaters	Yes			
Hurricane Beaters	Optional			
Quick Attach Beaters	Yes			
Hardox® Beaters	No			
MECHANICAL				
Beater Protection	Shear Bolt			
Hydraulic Brakes	Optional			
Steering Axle(s)	Optional			
Rear Drive Shaft Diameter (in / mm)	2 3/16 in 55 mm			
OPTIONAL UPGRADES				
Silage Kit	No			
Wall Extensions	Optional			
Scale and Rate Controller Systems	Optional			
Flight Protection System	Optional			