



LENGTH

Up to 34 ft

LEVEL CAPACITY

Up to 1006 ft³

HEAPED CAPACITY

Up to 1258 ft³

CARRYING CAPACITY

Up to 100,000 lbs

EMPTY WEIGHT

Up to 32,000 lbs

SUSPENSION

Spring or Hydraulic

WIDE BODY SPREADER

THE RIGHT TECHNOLOGY FOR THE MOST EFFICIENT FIELDWORK.

Whether you operate a family farm or a large agricultural enterprise, JBS Wide Body Spreaders can handle all types of manure.

Among the largest in today's market, they come in tandem and tridem axle models, feature highly maneuverable suspensions, and boast carrying capacities of up to 100,000 lbs.

With our optional bolt-on silage kits, our Wide Body Spreaders are workhorses during silage season and ideal for stockpiling manure in the off-season. Able to spread all types of manure in all kinds of conditions, our equipment is built to handle any fieldwork you need to be done quickly and efficiently.

WIDE BODY SPECIFICATIONS

	VMWB2448 -23	VMWB2648 -34	VMWB3048 -36	VMWB3048 -48	VMWB3048 -50	VMWB3448 -48	VMWB3448 -50
Dimensions							
Overall Length	10.5 m 413 in	11.1 m 437 in	12.32 m 485 in	13.6 m 534 in	13.6 m 534 in	14.8 m 582 in	14.8 m 582 in
Overall Height	3.6 m 140 in	3.7 m 145 in	3.7 m 146 in	3.7 m 146 in	3.7 m 146 in	4.2 m 167 in	4.2 m 167 in
Overall Width	3.2 m 125 in	3.2 m 125 in	3.2 m 125 in	3.2 m 125 in	3.2 m 125 in	3.2 m 125 in	3.2 m 125 in
Inside Box Width	2.2 m 88 in	2.2 m 88 in	2.2 m 88 in	2.24 m 88 in	2.2 m 88 in	2.2 m 88 in	2.2 m 88 in
Inside Box Length	6.7 m 264 in	7.3 m 288 in	8.5 m 336 in	8.5 m 336 in	8.5 m 336 in	9.8 m 384 in	9.8 m 384 in
Load Height	2.8 m 111 in	3.0 m 117 in	3.0 m 114 in	3.0 m 117 in	3.0 m 119 in	3.0 m 116 in	3.0 m 119 in
Level Capacity	20.1 m ³ 710 ft ³	22.7 m ³ 800 ft ³	25.2 m ³ 890 ft ³	25.2 m ³ 888 ft ³	25.2 m ³ 888 ft ³	28.5 m ³ 1,006 ft ³	28.5 m ³ 1,006 ft ³
Heaped Capacity	25.2 m ³ 888 ft ³	27.6 m ³ 975 ft ³	31.4 m ³ 1,110 ft ³	31.4 m ³ 1,110 ft ³	31.4 m ³ 1,110 ft ³	35.6 m ³ 1,258 ft ³	35.6 m ³ 1,258 ft ³
Carrying Capacity	46,000 lbs 20,865 kg	68,000 lbs 30,844 kg	72,000 lbs 32,659 kg	96,000 lbs 43,545 kg	100,000 lbs 45,359 kg	96,000 lbs 43,545 kg	100,000 lbs 45,359 kg
Empty Weight	24,500 lbs 12,020 kg	27,700 lbs 12,564 kg	23,500 lbs 10,659 kg	25,000 lbs 11,340 kg	26,500 lbs 12,020 kg	30,500 lbs 13,835 kg	32,000 lbs 14,515 kg
Standard Features							
Box Construction	10 Gauge						
Suspension	Spring	Spring	Spring	Spring	Hydraulic	Spring	Hydraulic
Axle	Tandem		Tridem				
Tire Size	700/40-22.5	750/45R-26.5	700/40-22.5	750/45R-26.5			
Tire Options	No	Yes	No	Yes	Yes	No	No
End Gate	Guillotine						
Bulkhead	Standard						
Hitch Type - Standard or Equal Angle	Yes						
Decal Package	Premium						
Apron/Floor							
Floor Chain - Long-Link 5/8" Grade 100	Yes						
Galvanized & Removable Cross Slats	Yes						
Floor Drive	Dual						
Planetary Drive	Optional		Yes				
UHMW Plastic Floor	Yes						
Steel Idler Sprockets w/Bronze Brushings	Yes						
Beaters							
Vertimax Vertical Beaters	Yes						
Hurricane Beaters	Optional						
Quick Attach Beaters	Yes						
Hardox® Beaters	Optional						
Mechanical							
Beater Protection	Shear Bolt						
Hydraulic Brakes	Optional			Yes			
Steering Axle(s)	Optional			Yes			
Rear Drive Shaft Diameter	55 mm 2 3/16 in			61.9 mm 2 7/16 in			
Add Ons							
Silage Kit	Optional						
Wall Extensions	Optional						
Scale & Rate Controller	Optional						
Flight Protection System	Optional						